

su sam – Log on as user **sam**
su - sam – Log on as **sam**, and execute his profile too
tail filename1 – Display last few lines of **filename1**
tail -50 filename1 – Display last fifty lines of **filename1**
tail -f – Continually reads updating file; Great for monitoring a log file while being written
tar -cvf /dev/rmt0c /usr/bin/* – Tape archive utility; Copies all files in **/usr/bin** directory to tape device **/dev/rmt/**
tar -xvf /dev/rmt0 /usr/bin/ – Extracts all files from tape device **/dev/rmt0** and writes them to **/usr/bin/**
tar -tvf /dev/rmt0c – Read tape on device **/dev/rmt/0c** and lists contents in verbose mode
tee – Used in scripts to split output to two outputs. Usually used with a pipe command (**()**)
tee -a /tmp/filename1 – Append the output to **filename1** without overwriting its original content
telnet hostb – Create a remote terminal on **hostb**
touch filename1 – Creates an empty file named **filename1**; Changes modification time to current time if the file already exists
uname -a – Lists O/S revision, host name, hardware
uncompress filename1 – Uncompresses file with **.Z** suffix, created by **compress** command previously
uptime – Displays current time, time logged-in, number of users etc
users – Displays current logged-in users in a listing
uucp – UNIX-to-UNIX copy utility; See **man** pages
view filename1 – A read only version of vi editor
w – Combination of uptime, who and ps -a commands
wall – Write to all; Allows entry of message to be sent to line 25 of all terminals; End message with a CTRL-D command
wc -l filename1 – Utility that counts the number of lines in **filename1**
wc -c filename1 – Utility that counts the number of bytes in **filename1**; **-m** provides number of characters
wc -w filename1 – Utility that counts the number of the words in **filename1**
whence filename2 – Prints path name location of executable **filename2**
which filename2 – Similar to whence command
who – Displays login name, terminal name, date, and time of login, of users currently logged in
who am i – Displays effective user id of user
who -b – Displays date/time of last reboot
who -r – Displays current system run level

Visual Editor Commands and Navigation

Cursor Movement

h,j,k,l	Move left, down, up and right
O,\$	Jump to front, end of line
w	Skip to next word
CTRL-D	Down one page
CTRL-U	Up one page
G	Skip to end of file
1G	Skip to top of file
CTRL-R or CTRL-L	Refresh screen.

Searching

/ text	Search forward for text.
? text	Search backward for text.
n	Repeat search after find.

Line Numbering

CTRL-G	Display current line number.
:99	Move to line number 99 .

Inserting Text

a	Append after cursor
A	Append to end of line
i	Insert before cursor
I	Insert at beginning of line
o	Open new line below cursor
ESC	Terminate edit mode return to command mode

Changing Text

cw	Change word
cc	Change whole line
C	Change text to end of line
dd	Delete line
5dd	Delete current line and next 4
D	Delete to end of line
u	Undo last change
U	Restore current line

Moving Text

yy	Yank a copy of current line
p	Insert the previously yanked line

Saving and Exiting

ZZ	Save and exit file
:wq	Same as ZZ
:q!	Exit without saving
:n	Go to next file to be edited
:w filename1	Save edited file as filename1

Symbols

>	Redirect output
<	Redirect input
>>	Append to file
 	Pipe Output
&	Run process in background
;	Separate commands
*	Match any character(s)
?	Match a character

Common UNIX System V Commands Pocket Guide

Download this and other pocket guides in addition to other articles from our website:
www.solutionbeacon.com

Contact:
solutions@solutionbeacon.com

Solution Beacon LLC reserves the right to revise this document at any time without obligation to notify any person of such revisions. Solution Beacon does not warrant that this document is error-free. In no event shall Solution Beacon be liable for any consequential or incidental damages, including but not limited to loss of business profits. Any other commercial product names herein are trademarks, registered trademarks, or service marks of their respective owners.



Real Solutions for the Real World.®

Common UNIX 5VR4 Commands

man – Online UNIX manual (“man-pages”); Gives detailed instructions on all of the commands listed here and a lot more; See **man man** for more

cat filename1 > filename2 – Overwrite contents of **filename2** with **filename1**

cat filename1 » filename2 – Append contents of **filename1** to **filename2**

cd /usr – Change current directory to **/usr**

cd .. – Change current directory to previous higher directory

cd – Change to home of current userid

chgrp group1 filename1 – Change group id to group 1 for **filename1**

chgrp -R group1 * – Change group id of all files in current and subdirectories to **group 1**

chmod ugo+rxw filename1 – Add read/write/execute permission to **filename1** for user/owner, group and others (world)

chmod o x filename1 – Remove execute from others (world)

chmod 751 filename1 – Set rwx for user/owner, group and others; r=4, w=2, x=1, rwx=7 rx=5, rw=6, wx=3, none=0; see **man** pages

chown sam filename1 – Change owner of file **filename1** to **sam**

chown -R sam * – Change owner to **sam** for all files in current and subdirectories

clear – Clear the terminal screen

compress filename1 – Compress file **filename1** and replace it with **filename1.Z**; See also **uncompress**

cp filename1 filename2 – Copy file **filename1** to **filename2** destroying the contents of **filename2**

cp -i * /usr/local/bin – Copy all files in current directory to **/usr/local/bin** directory; Prompt before overwriting files (i)

cpio – Copy file archives to disk/tape; See **man** pages

crontab -e – Edit crontab file for current user

crontab -e bill – Edit crontab file for user **bill**

crontab -l – List crontab entries for current userid

csh – Start the c shell process; See **man** pages

cut -d: -f1,5 /etc/passwd – Extract the 1st and 5th fields (username & real name) from file **/etc/passwd** where delimiter is colon

who | cut -d" " -f1 – List login names from who command

date – Display current date string

date +%D – Display current date, MM/DD/YY format

dd – Copy file(s) to/from raw devices; See **man** pages

df – Display free disk blocks and modes on file systems.

df -k – Display free space in kilobytes for mounted file systems

echo name – Displays literal “name” on screen

echo \$PATH – Displays PATH environment variable

ed/edit/ex – Alternative line editors, see **vi**

env – Displays current environment variables or allows setting

file filename1 – Determines and displays type of file for **filename1** (text, data, executable, directory, symbolic link...etc...)

find /usr/opt/bin -name "filename1*" -print – Starts searching in **/usr/opt/bin** for files starting with **filename1**; If found prints the full file names and continues searching subdirectories

find . -type f -print | xargs grep -i [PATTERN] – Recursive grep for a pattern in a file (searches through files in subdirectories)

find . ! -mtime <days> | /usr/bin/xargs rm -rf – Finds and removes files older than <days> specified

finger sam – Displays data about user session for **sam**

ftp solar – Establishes a File Transfer Protocol session over the network between current host and a host named **solar**; See **man** pages for additional ftp commands

grep jdoe /etc/passwd – Searches the file **/etc/passwd** searching for string “jdoe”; If found, displays

grep -i Sam filename1 – Search **filename1** for upper or lower case string of **Sam** and display lines found

groups sam – List groups that **sam** is a member of

head filename1 – Display first few lines of **filename1**

head -50 filename1 – Display first fifty lines of **filename1**

id – List current user id and any group ids

kill -9 1351 – Terminate process number 1351

ksh – Start Korn Shell command interpreter; See **man** pages; Preferred shell for most users

ln -s filename1 /usr/opt/filename2 – Create a symbolic link named **/usr/opt/filename2** that points to **filename1**; See **man** pages

lp -d lp1 filename1 – Print **filename1** on destination printer **lp1**

lpstat -d – Displays name of default printer, if any

lpstat -a – Lists printers accepting print requests

lpstat -s – Displays most everything regarding printing

lpstat -u sam – Displays status of **sam**’s print jobs

ls -al – Displays all files in wide listing

ls -al *.doc – Displays files ending with **.doc**

ls -al /bin/k* – Displays files starting with **k** in **/bin** directory

mail sam – Starts mail message to **sam**

mailx sam – Nicer looking mail utility

mkdir -p /usr/opt/dirx – Creates **dirx** below **/usr/opt**

make – Code compilation utility

mkdir dirx – Creates directory **dirx**

more filename1 – Displays single pages from **filename1** pausing after each page; Many options; See **man** pages

mv filename1 /usr/opt/ – Moves **filename1** to directory **/usr/opt**; Unlike the **cp** (copy) command, **mv** removes file from origin

netstat -i – Show the TCP/IP network interfaces

netstat -r – Show network route table

netstat -rn – Displays routing information but bypasses hostname lookup

netstat -a | more – Show the state of all sockets

newgrp group1 – Changes current group to group 1

news – Displays unread files from **/usr/news** or **/var/news**

nice/renice – Adjusts process’ execution priority

passwd – Allows changing your login password

ps – Lists all of current user’s live processes

ps -ef – List all users processes that are executing

pwd – Displays current working directory you are in

rcp filename1 hostb:/usr/local/bin – Copies **filename1** from current host system to **hostb**, and places it in the **/usr/local/bin** directory; The **.rhosts** or **hosts.equiv** files must be setup to allow action

rksh – Starts restricted Korn Shell session

rlogin hostb – Logs into remote host name **hostb**

rm filename1 – Deletes **filename1** from the disk without recourse

rm -i filename1 – Deletes **filename1** after prompting for verification

rmdir dirx – Deletes directory **dirx**

rmdir -r dirx – Deletes directory and all contents

rsh – Restricted version of Bourne Shell for security

sar – System Activity Reporter

sh – Bourne Shell command interpreter; Alternative to Korn Shell and C shell but is the default on most systems; Older version that is losing popularity

sleep 3 – Pauses for 3 seconds and continues

stty sane – Attempts to restore terminal settings after they are hosed; Use CTRL-J with this command

stty erase ^H – Use to reset backspace/delete; **^H** is the key you may want to use for backspace/delete; Typically the backspace key itself