Trustworthy partnership

Dendrolight Latvija Ltd. is the first and the only licensed DendroLight® material manufacturer in the world.

Dendrolight Latvija Ltd. is part of privately owned Group of Latvian enterprises that occupies more than 12 000 m2 of production area and has been sucesfully operating in European markets for more than 20 years.

Hi tech of wood processing


Innovative approach to wood engineering and continuous product research secures the most advanced manufacturing process and top quality production standards.

ECO responsibility

Dendrolight® Latvija is taking ECO responsibility to another level by producing environmentaly friendly products with CO₂ neutral (++) and ultra energy and resources saving approach.

Convenient logistics

Dendrolight Latvija plant is situated in Ventspils, Latvia, which is one of the main transit centers in Eastern Europe, providing convenient sea, rail and road logistics.





DendroLight® middle layer DendroLight® 3-layer panel DendroLight® door blank DendroLight® building block DendroLight® acustic panel



Wooden windows Doors and facades Sliding systems Carpentry and furniture Modular houses Construction



Insulating glass production



DendroLight® BUILDING BLOCK

www.dendrolight.lv www.ekomajas.lv www.arbo.lv





DendroLight®

DendroLight® is unique solid wood material that grants extra lightness and stability to natural solid wood.

The key feature of the material lies in the manufacturing process of the DendroLight® middle layer which is made of unique spruce, pine or aspen tree profiles. The profles are glued together in perpendicular angles forming DendroLight® middle layer block, which can then be band sawed into middle layer sheets.

MAIN MATERIAL ADVANTAGES

- Reduced weight (270 477 kg/m³ for middle layer; 360 - 477 kg/m³ for panels)
- Low swelling characteristics (down to 0,5%, depending on thickness and type of deck layer)
- High stiffness (low E-module: 25 mm 2290 N/mm²; 60 mm 1240 N/mm²)
- High and homogeneous surface stability
- No internal tensions (if not created by deck layers)
- High internal bound (0,44 N/mm²)
- Good screw hold characteristics (760-950 N/mm² for surface: 530 N/mm² for side)
- Comprehensive strength (2 N/mm²)
- Low glue content (4 5%)
- Cost effective logistics and storage
- Easy processing
- Environment friendly material







Building Block

DendroLight® Building block represents new construction concept. It is light, easy, natural and strong. It allows replacing different kinds of construction materials with singe DendroLight® concept that shortens construction time lines and decreases spenditures on labour costs.

Let innovative technologies enrich your life with the best qualities of wood.


GENERAL TECHNICAL DATA

DendroLight® Building block is made of DendroLight® middle layer block and solid wood or plywood decking.



Building block combines such properties as light weight (\sim 330 kg/m3), tremendous strength and good heat and sound insulation.

(mm)		
Width	1300	650
Length	3000	
Thickness	72-112 mm + deck (18mm-25mm)	
Deck materials	solid wood	plywood



Application

DendroLight® building blocks are well suited for:

- Floor ceiling panels
- Internal and external wall elements
- Roof panels











ALSO AVAILABLE:

- DendroLight® Middle Layer Material
- DendroLight® 3-Layer Panel
- DendroLight® Door Blank
- DendroLight® Building Block
- DendroLight® Acoustic Panel

For additional information contact your local DendroLight® area manager or distributor listed on our official web site

www.dendrolight-latvia.com